

K Series:

Specifications	K8	K10	KW12	KSub
Configuration	Trapezoidal 2-way	Multipurpose 2-way	Multipurpose 2-way	4th Order Bandpass
Transducers				
Low-Frequency	8" cone transducer	10" cone transducer	12" cone transducer	2 x 12" cone transducers
High-Frequency	1.75" diaphragm compression driver	1.75" diaphragm compression driver	1.75" diaphragm compression driver	
Frequency Response (-6dB)	66 Hz – 18 kHz	60 Hz – 18 kHz	52 Hz – 18 kHz	48 Hz – 134 kHz
Frequency Range (-10dB)	61 Hz – 20 kHz	50 Hz – 20 kHz	48 Hz – 20 kHz	44 Hz – 148 kHz
Nominal Coverage (-6dB)	105° conical	90° conical	75° conical	-
Maximum SPL	127 dB peak	129 dB peak	131 dB peak	130 dB peak
Amplifier				
Power Output	1000 W continuous Class D (500 W LF, 500 W HF) 2000 W peak			1000 W continuous Class D (2x500 W) 2000 W peak
Enclosure				
Material	Impact resistant ABS			Painted birch plywood
Finish	Black paint			Black textured paint
Grille	Rugged Powder-Coated Steel Grille			-
Dimensions (HWD)	17.7" x 11" x 10.6" 450mm x 280mm x 269mm	20.4" x 12.6" x 11.8" 519mm x 320mm x 300mm	23.7" x 14" x 14" 603mm x 356mm x 356mm	26" x 14" x 28.1" with castors 665mm x 356mm x 714mm with castors
Weight (Net)	12.2kg	14.5kg	18.6kg	33.6kg
Available Accessories	K8 TOTE K8 YOKE, K SERIES M10 KIT	K10 TOTE K10 YOKE, K SERIES M10 KIT	K12 TOTE K12 YOKE, K SERIES M10 KIT	KSub COVER