LOVAC® METAL ENCLOSURE
INNER AND GLASS DOOR

Brand : **LOVAC®**
Color : RAL 7032 and RAL 7035
Protection Degree : IP 66 to IEC 60529:2001
Surface Finishing : Epoxy polester powder coating
Mounting plate : Zinc-coated steel 2mm thick
Body and Door : Sheet Steel 1.2mm till size LVIG50 4025 , above 1.5mm
: Tempered Glass
Supply Includes : Mounting Plate, Lock, Gland plate, Sealing gasket and Fixing accessories

Item	Model	Height (mm)	Width (mm)	Depth (mm)	No.of Lock
1	LVIG40 3015	400	300	150	1
2	LVIG40 3020	400	300	200	1
3	LVIG40 3025	400	300	250	1
4	LVIG40 4020	400	400	200	1
5	LVIG40 4025	400	400	250	1
6	LVIG50 4015	500	400	150	1
7	LVIG50 4020	500	400	200	1
8	LVIG50 4025	500	400	250	1
9	LVIG50 5020	500	500	200	1
10	LVIG50 5025	500	500	250	1
11	LVIG50 5030	500	500	300	1
12	LVIG60 4020	600	400	200	2
13	LVIG60 4025	600	400	250	2
14	LVIG60 4030	600	400	300	2
15	LVIG60 5020	600	500	200	2
16	LVIG60 5025	600	500	250	2
17	LVIG60 5030	600	500	300	2
18	LVIG60 6020	600	600	200	2
19	LVIG60 6025	600	600	250	2
20	LVIG60 6030	600	600	300	2
21	LVIG70 5020	700	500	200	2
22	LVIG70 5025	700	500	250	2
23	LVIG70 5030	700	500	300	2
24	LVIG80 6020	800	600	200	2
25	LVIG80 6025	800	600	250	2
26	LVIG80 6030	800	600	300	2
27	LVIG80 8025	800	800	250	2
28	LVIG80 8030	800	800	300	2
29	LVIG100 6020	1000	600	200	2
30	LVIG100 6025	1000	600	250	2
31	LVIG100 6030	1000	600	300	2
32	LVIG100 8025	1000	800	250	2
33	LVIG100 8030	1000	800	300	2
34	LVIG120 6025	1200	600	250	2
35	LVIG120 6030	1200	600	300	2
36	LVIG120 8025	1200	800	250	2
37	LVIG120 8030	1200	800	300	2

SPECIFICATIONS ARE SUBJECT TO CHANGES WITHOUT PRIOR NOTICE