



# 36CH Network Video RYWtfXYf

## SCABJF3636A



Model NO.	SCANVR3636A
<b>SYSTEM</b>	
Main Processor	ARM Cortex A7 Quad-core Processor
Operating System	Embedded LINUX
<b>VIDEO</b>	
Input	36 Channel, Support 4096×2160, 2592×1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc, Incoming Bandwidth: 300MB
Output	1 VGA, 1 HDMI
<b>AUDIO</b>	
Input	1 Port RCA
Output	1 Port RCA
<b>ALARM</b>	
Sensor Input	NO
Output	NO
Motion Detection	36 channel
Email Alarm	Support
<b>DISPLAY</b>	
VGA	Resolution:1920x1080/1280x1024/1280x720
HDMI	Resolution: 4K 3840X2160/1920X1080/1280X1024/1280X720
Display Split	36CHxD1/25CHxD1/16CHxD1/9CHxD1/4CHxD1/1CHx1080P /1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k
Digital Zoom	YES
OSD	Camera Title, Time, Video Loss, Recording, Motion Detection
<b>RECORDING</b>	
Video Compression	H.265/H.264
Resolution	4k(4096×2160),5MP(2592×1944),4MP(2688×1520),3MP(2048×1536), 1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (704×576/704×480)

<b>Model NO.</b>	<b>SCANVR3636A</b>
Record Rate	PAL:4k@30×25fp,5MP@36×25fp,4MP@36×25fp,3MP@36×25fp,1080P@36×25fp,960P@36×25fp,720P@36×25fp,D1@36×25fp NTSC:4k@30×30fp,5MP@36×30fp,4MP@36×30fp,3MP@36×30fp,1080P@36×30fp,960P@36×30fp,720P@36×30fp,D1@36×30fp
Record Mode	Manual/Timer/Motion Detection
<b>PLAYBACK &amp; BACKUP</b>	
Local Sync Playback	4 channel x 4K
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
Backup Mode	USB Device/Network
<b>NETWORK</b>	
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface
Network Functions	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Search, P2P
Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows XP / Windows Vista / Windows 7/ Windows 8
Cloud Support(P2P)	YES
Smart Phone	iPhone, iPad, Android, Android Pad
<b>STORAGE</b>	
Interface Type	2 SATA Interface
Capacity	Up to 12TB capacity
<b>GENERAL</b>	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa,German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces ,1 USB 3.0 Interface
Power Supply	DC12V/3A
Working Environment	-10~55°C/10~90%
Dimension(W×D×H)	354mm×263mm×50mm
Weight	3.5KG (without HDD)

\*Due to product enhancement, Sin Chew Alarm reserved the right to change/modify specifications without prior notice.